



RC 20^{XP} DRUM BRUSH CHIPPER



Diesel Powered Chipper

- Powerful 225 HP 6 cylinder, diesel engine (John Deere 6068T- ATAAC)
- Huge 20" diameter chipping capacity
- Intake rate up to 105 ft/minute

RC 20^{XP} DRUM BRUSH CHIPPER

General:

Length	230"/242" Adjustable Tongue
Weight	12,000 lbs (at 225 HP)
Height	114"

Engine Options:

Make/Model	John Deere 6068T-ATAAC
Type of fuel	Diesel
HP	225
Peak torque (lb-ft)	
Number of cylinders	6
Cooling	Water + ATAAC

Capacities:

Fuel Tank	65 gallon
Hydraulic tank	20 gallon

Cutting System:

Cutter Drum	36' drum x 20" wide
Knives	(4) .625" X 5.5" X 10" long double edged knives
Bedknife	(4) .75" x 6.75 X 25.25" grade A8 steel bedknives

Other:

- 30.75" X 20.5" infeed opening
- Variable speed fan control
- 114" discharge height
- Infeed floor to table length - 98" (to knife) 61" (to feed wheel)
- 360 degree chute rotation
- Hydraulic clutch engagement
- Tandem, 7000# torsion axel
- Hydraulic jack
- Pintle hitch
- 12 volt electrical

Safety:

- Neutral start interlocks are provided on both chipper engagement & feed system
- Feed chute & feed control bar meet OSHA & ANSI Z133 safety standards; protecting operators from both the feed & cutting mechanisms
- Feed control bar is designed with minimized linkages & minimized wear points to provide reliable control of the feed rollers
- Cutter drum access panel is held in place by six bolts, providing ample time for cutter drum to stop for maintenance purposes
- Cutter drum locking pin holds drum in place for maintenance & has integral device to prevent closing housing when pin is engaged
- LED lighting provides reliable visibility to surrounding traffic
- Discharge chute rotation is infinitely adjustable and is self-holding in any position

For sales and service, contact your local Rayco Dealer:



Trenchless Utility Equipment Inc.
2070 Queensway Drive,
P.O. Box 1338 Burlington, ON L7R 4L9
Ph: (905) 634-0669 Fax: (905) 634-6685
info@trenchlessutility.com