



## RC 6D CHIPPER



Powered by a 25 HP Kohler V-twin engine with a capacity for 39.5 ft/lbs @ 2,800 rpm, the RC 6D Brush Chipper generates high performance, while providing long-life and easy maintenance. The entire Rayco line of brush chippers is manufactured in the USA at Rayco's state-of-the-art facilities. Rayco supplies our authorized Rayco dealers with quality components to guarantee that service and replacement parts are readily available.

The RC 6D Brush Chipper is ideal for rental applications due to its enhanced safety features and economical performance. In addition, its overall simplicity leads to reduced maintenance costs. Keeping the chipper at the correct rpm level creates a more uniform chip, uses less fuel, and minimizes vibration, which reduces wood-shifting and enhances operator safety.

### Special Features:

- Variable Speed Feed Control
- High Capacity, Dual Element Air Cleaner
- Weighted Feed Roller
- Feed System Brake
- 360° Rotating Discharge Chute
- Telescoping Tongue
- Folding In-feed Table

RC 6D General Specifications: Standard	
Length	102"
Height	94"
Width at 25 HP	52.5"
Weight at 25 HP	1,960 lbs
Engine Options: Standard	
Make/Model	Kohler CH730
Type of fuel	Gasoline
HP	25
Peak torque (lb-ft)	39.5 @ 2,800
Number of cylinders	V-twin
Cooling	Air
Capacities: Standard	
Fuel Tank	7.6 gallon
Hydraulic tank	7.6 gallon

# RC 6D CHIPPER CONTINUED

<b>Cutting System:</b>	<b>Standard</b>
<b>Cutter</b>	24" disc x 1.25" thick
<b>Speed</b>	1,722 rpm
<b>Knives</b>	0.625" x 4.5" x 8" lg., double-edged
<b>Quantity of Knives</b>	2
<b>Bedknife</b>	(4) Edge, 3/4" x 5" x 6.6", A8
<b>Clutch engagement</b>	Belt idler
<b>Feed/Discharge System:</b>	
<b>Chipping capacity</b>	6" diameter
<b>In-feed opening</b>	6" x 6"
<b>In-feed floor/table length</b>	64" (to knife) 59" (to feed wheel)
<b>Feed table height</b>	30"
<b>Feed roller style</b>	(1) horizontal roll (8" diameter)
<b>Downpressure</b>	Springs
<b>Intake rate</b>	0-180 ft /minute
<b>Discharge height</b>	94"
<b>Rotation</b>	360°
<b>Chassis:</b>	
<b>Frame</b>	7-gauge plate
<b>Tires</b>	18.5 x 8 5/8"
<b>Axle/Suspension</b>	2200# Torsion axle
<b>Hitch</b>	2" ball
<b>Jack options:</b>	
<b>#1-Standard</b>	500# w/caster
<b>Electical:</b>	
<b>System Voltage</b>	12V
<b>Lights</b>	Stop, tail, turn, license, side marker

For sales and service, contact your local Rayco Dealer:



Trenchless Utility Equipment Inc.  
 2070 Queensway Drive,  
 P.O. Box 1338 Burlington, ON L7R 4L9  
 Ph: (905) 634-0669 Fax: (905) 634-6685  
 info@trenchlessutility.com