





For sales and service
contact your local dealer:



Trenchless Utility Equipment Inc.
2070 Queensway Drive,
P.O. Box 1338 Burlington, ON L7R 4L9
Ph: (905) 634-0669 Fax: (905) 634-6685
info@trenchlessutility.com

Length x Diameter	Depth Range	Battery Type	Temp. Rating	Weight	MSRP*
DFT: Dual Frequency (1.5 / 33 kHz) For use with the Mark 5 System					
					
15 in. x 1.25 in. 38 cm x 3.125 cm	45 ft 13.7m	2 C-cell alkaline 20 hours awake 200 hours sleep	220°F 104°C	1.4 lb 635 g	
DS: Short Range (Blue) Mark 3/4 compatible.					
					
8 in. x 1.00 in. 20 cm x 2.5 cm	15 ft 4.6 m	1AA-cell alkaline 12 hours awake 50 hours sleep	180°F 82°C	8.4 oz 240 g	
DT: Standard Range (Yellow) Mark 3/4/5 compatible.					
					
15 in. x 1.25 in. 38 cm x 3.125 cm	40 ft 12.2 m	2 C-cell alkaline 30 hours awake 200 hours sleep	220°F 104°C	1.4 lb 635 g	
DX: Long Range (Red) Mark 3/4/5 compatible.					
					
15 in. x 1.25 in. 38 cm x 3.125 cm	70 ft 21.3 m	2 C-cell alkaline 20 hours awake 200 hours sleep	220°F 104°C	1.4 lb 635 g	

D4X: DX with Extended Life (Red) Mark 3/4/5 compatible.

19 in. x 1.25 in. 48 cm x 3.125 cm	70 ft 21.3 m	4 C-cell alkaline 40 hours awake 400 hours sleep	220°F 104°C	1.4 lb 635 g	
--	-----------------	---	----------------	-----------------	--

DXP: Long Range with 0.1% Pitch (Magenta) Mark 3/4/5 compatible. Pitch range -10% to 10%. For level drilling use only.

15 in. x 1.25 in. 38 cm x 3.125 cm	70 ft 21.3 m	2 C-cell alkaline 20 hours awake 200 hours sleep	220°F 104°C	1.4 lb 635 g	
--	-----------------	---	----------------	-----------------	--

D4XP: D4X with 0.1% Pitch (Magenta) Mark 3/4/5 compatible. Pitch range -10% to 10%. For level drilling use only.

19 in. x 1.25 in. 48 cm x 3.125 cm	70 ft 21.3 m	4 C-cell alkaline 40 hours awake 400 hours sleep	220°F 104°C	1.85 lb 840 g	
--	-----------------	---	----------------	------------------	--

DC: Cable Transmitter (Green) Mark 3/4 compatible.

15 in. x 1.25 in. 38 cm x 3.125 cm	140 ft 42.7 m	12V to 28V DC cable power	180°F 82°C	1.2 lb 545 g	
--	------------------	---------------------------------	---------------	-----------------	--

DCP: DC with 0.1% Pitch (Magenta) Mark 3/4 compatible.

15 in. x 1.25 in. 38 cm x 3.125 cm	140 ft 42.7 m	12V to 28V DC cable power	180°F 82°C	1.2 lb 545 g	
--	------------------	---------------------------------	---------------	-----------------	--