

General Specifications

Physical (no case or accessories):

Height.....	6.30 in.	160 mm
Width.....	9.45 in.	240 mm
Depth.....	2.36 in.	60 mm
Weight.....	3 lbs.	1.3 kg

Physical (case and accessories)

Height.....	7.80 in.	198 mm
Width.....	11.0 in.	279 mm
Depth.....	6.5 in.	165 mm
Weight.....	6 lbs.	2.6 kg

Environmental

Operating Temp.....	0°C to 50°C	32°F to 122°F
Storage Temp.....	-20°C to 60°C	-4°F to 140°F
Humidity.....	95% max. relative, non-condensing	
Vibration.....	IEC 68-2-6	
Shock (Bump).....	IEC 68-2-29	
Drop.....	IEC 68-2-27	
Moisture Rating.....	IP 54	

Power

Internal.....	Rechargeable, 7.2V nickel metal hydride battery pack
External.....	12 VAC or VDC, 1250mA power supply
Operating Time.....	>6 hours without backlight
Display.....	320 X 240 dot-matrix liquid crystal display with CCFL backlighting

Time Domain Reflectometer (loaded and non-loaded cable)

Horizontal Resolution

<2000 ft.....	<0.25 ft at 99.0% VOP, <0.07 ft at 30.0% <0.07 m at 99.0% VOP, <0.02 m at 30.0%
>2000 ft.....	1 foot at any VOP 0.1 meter at any VOP

Vertical Resolution.....	14 bits with 137 dots displayed
Vertical Sensitivity.....	>65dB

Output Signal.....	2ns, 25ns, 100ns, 500ns, 1.5ms, 4.4ms and 330 ms
--------------------	-----------------------------------------------------

Output Balance.....	Variable from 80□ to 120□
Distance Accuracy.....	±0.5 ft plus ±0.01% of reading ±0.15 m plus ±0.01% of reading

Maximum Range

Live Waveform.....	63,700 ft (19,400 m) at 99.0% VOP 38,600 ft (11,700 m) at 60.0% VOP <i>Range varies with VOP. Maximum testable cable length varies with pulse width and cable type.</i>
--------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Input Protection.....

400 VAC or VDC up to 60 Hertz

Velocity of Propagation Two user-selectable display formats.

VOP (%) ranging from 30.0% to 99.0%	
Loaded Cable.....	VOP (%) ranging from 0.8% to 20.0%
V/2 ranging from 45.0 to 148.4m/ms or 147.5 to 486.9 ft/ms	
Loaded Cable.....	V/2 ranging from 1.2 to 30.0 m/ms or 3.9 to 98.4 ft/ms

Waveform Storage

Standard.....	8 SUPER-STORE waveforms at 6144 samples each
---------------	----------------------------------------------

Standard Accessories

Operator's Manual, 12VDC charger, nylon carry/accessory bag, shoulder strap, 2 sets telephone connection leads plus ground lead, pair shorting strap, and VOP card.

Options

Extended waveform storage, 32 waveforms, and extended TDR noise filters.

Optional.....	32 SUPER-STORE waveforms at 6144 samples each
---------------	-----------------------------------------------

Software Noise Filters

Standard.....	8x, 50/60 Hz
Optional.....	4x, 8x, 16x, 32x, 64x, 128x, 50/60Hz

Resistance Fault Locator

Location Range.....	0 to 100 kft
Resistance Fault Range.....	0 to 50M□
Accuracy	
3-Wire Test.....	±0.25% of DTS ±0.4ohms
4-Wire Test.....	±0.25% of DTS ±0.25ohms
Kupfmuller Test.....	±1.0% of DTS ±1 ohm

Noise/Balance Measurements

Longitudinal Balance.....	40 to 62 dB
Frequency.....	1004 Hz
Resolution.....	1 dB
Accuracy.....	±2 dB
Noise Metallic.....	0 to 50 dBmC
Transverse Noise.....	-90 to -40 dBmp
Resolution.....	1 dB
Accuracy.....	±2 dB
Power Influence.....	40 to 100 dBmC
Longitudinal Noise.....	-50 to 10 dBmp
Resolution.....	1 dB
Accuracy.....	±2 dB

Multi-Meter

DC Voltage.....	0 to 400V
Resolution.....	0.1V
Accuracy.....	1% ±0.1V
AC Voltage.....	0 to 400V
Resolution.....	0.1V
Accuracy.....	1% ±0.1V
Foreign Battery.....	2 to 400V
Resolution.....	0.1V
Accuracy.....	1% ±0.1V

Resistance

0 to 2 k□	
Resolution.....	0.1□
Accuracy.....	0.2%±0.2□
2k□ to 10k□	
Resolution.....	1□
Accuracy.....	0.2%±1□

Insulation Resistance

0.00M□ to 100M□	
Resolution.....	0.01M□
Accuracy.....	±1%
Loop Current.....	0 to 120mA
Resolution.....	0.1mA
Accuracy.....	5% ±0.1mA



For Sales & Service Contact: Trenchless Utility Equipment Inc.
2070 Queensway Drive, Box 1338
Burlington, ON L7R 4L9
Ph: (905) 634-0669 Fax: (905) 634-6685



5101 N. 57th Street – Lincoln, NE – 68057 – USA – email@riserbond.com – www.riserbond.com

Phone (402) 466-0933 – U.S. Toll Free (800) 688-8377 – FAX (402)-466-0967