


## Sewer Sonde Technical Specification

---

<b>Description</b>	Sewer Sonde - Sonde Transmitter.
<b>Part No.</b>	10/SB0337-8 - 8 kHz. 10/SB0337-33R - 33 kHz.
<b>Physical</b>	
Construction	Polypropylene.
Dimensions	16.8 x 6.4 cm (6.6 x 2.5 in.).
Weight	500 g (1.1 lb).
Shipping Weight	1 kg (2.2 lb).
<b>Operating Frequency</b>	8 kHz (8192 Hz) or 33 kHz (32768 Hz).
<b>Signal</b>	Continuous/pulsed (dependant on battery polarity).
<b>Depth Range</b>	Down to 8 m (26 ft).
<b>Batteries</b>	1 x 6LR61 (9V) alkaline. 15 hours life, continuous use.
<b>Operating Temperature Range</b>	-15°C to +50°C (+5°F to +122°F).
<b>Submersion Level</b>	2 m water (0.2 bar pressure).
<b>Thread</b>	M10 male.
<b>Miscellaneous</b>	
Compatibility	Recommended Radiodetection Receivers: RD300 and RD400 range.
Quality Control	BS5750/ISO 9001/EN29001.
EMC	☑ Complies with European EMC Directive 89/336/EEC.
Warranty	12 months.



**Radiodetection**

Riser Bond    Dielectric Technologies  
Bicotest      Pearpoint      Telespec

Contact Your Radiodetection Dealer

**TRENCHLESS**  
UTILITY EQUIPMENT INC.

2070 Queensway Drive, P.O. Box 1338 Burlington,  
ON L7R 4L9 Ph: (905) 634-0669 Fax: (905) 634-6685  
info@trenchlessutility.com

---

Radiodetection Ltd  
Western Drive  
Bristol BS14 OAZ, UK  
Tel: +44 (0) 117 976 7776  
Fax: +44 (0) 117 976 7775  
email:sales.uk@radiodetection.spx.com  
<http://www.radiodetection.com>



**Radiodetection**

Riser Bond Dielectric Technologies  
Bicotest Pearpoint Telespec

Radiodetection products are under continuous development and are subject to change without notice

All rights reserved

TS049EN0