


## Mega Mouse/Standard Sonde Technical Specification

---

<b>Description</b>	Mega Mouse - Sonde Transmitter. Standard Sonde – Sonde Transmitter
<b>Part No.</b>	<b>10/SC0412-33R-33 kHz.</b>
<b>Physical</b>	
Construction	High impact ABS.
Dimensions	10.5 x 3.9 cm (4.13 x 1.5 in.).
Weight	190 g (7 oz).
Shipping Weight	1 kg (2.2 lb).
<b>Operating Frequency</b>	8 kHz (8.192 kHz) or 33 kHz (32.768 kHz).
<b>Signal</b>	Continuous
<b>Depth Range</b>	Down to 5 m (16 ft).
<b>Batteries</b>	1 x LR6 (AA) 1.5 V alkaline. 20 hours life, continuous use.
<b>Operating Temperature Range</b>	-15°C to +50°C (+5°F to +122°F).
<b>Submersion Level</b>	20 m water (2 bar pressure).
<b>Thread</b>	M10 male.
<b>Miscellaneous</b>	
Compatibility	Recommended Radiodetection Receiver: C.A.T. (Mega Mouse) Recommended Radiodetection Receivers: RD300 & RD400 range (Standard Sonde)
Quality Control	BS5750/ISO 9001/EN29001.
Approvals	CE 8KHz model complies with European EMC Directive 89/336/EEC, 33KHz model complies with European R&TTE directive 1999/5/EC
Warranty	12 months.



**Radiodetection**

Riser Bond    Dielectric Technologies  
Bicotest      Pearpoint      Telespec

Contact Your Radiodetection Dealer

**TRENCHLESS**  
UTILITY EQUIPMENT INC.

2070 Queensway Drive, P.O. Box 1338 Burlington,  
ON L7R 4L9 Ph: (905) 634-0669 Fax: (905) 634-6685  
info@trenchlessutility.com