


Super Sonde Technical Specification

Description	Super Sonde - Sonde Transmitter.
Part No.	10/SB0338-8 - 8 kHz. 10/SB0338-33R - 33 kHz.
Physical	
Construction	Polypropylene.
Dimensions	31.8 x 6.4 cm (12.5 x 2.5 in.).
Weight	900 g (1.98 lb).
Shipping Weight	1 kg (2.2 lb).
Operating Frequency	8 kHz (8192 Hz) or 33 kHz (32768 Hz).
Signal	Continuous/pulsed (dependant on battery polarity).
Depth Range	Down to 15 m (50 ft).
Batteries	1 x 6LR61 (9V) alkaline. 5 hours life, continuous use.
Operating Temperature Range	-15°C to +50°C (+5°F to +122°F).
Submersion Level	2 m water (0.2 bar pressure).
Thread	M10 male.
Miscellaneous	
Compatibility	Recommended Radiodetection Receivers: RD300 and RD400 range.
Quality Control	BS5750/ISO 9001/EN29001.
EMC	☑ Complies with European EMC Directive 89/336/EEC.
Warranty	12 months.



Radiodetection

Riser Bond Dielectric Technologies
Bicotest Pearpoint Telespec

Contact Your Radiodetection Dealer

TRENCHLESS
UTILITY EQUIPMENT INC.

2070 Queensway Drive, P.O. Box 1338 Burlington,
ON L7R 4L9 Ph: (905) 634-0669 Fax: (905) 634-6685
info@trenchlessutility.com