

Underground Puller



US DEALER



**GLOBAL
MACHINERY**
SPECIALIZED UTILITY EQUIPMENT

Underground puller



KE-SP 2030

General specifications:

- Pulling force – 6,700 lbs
- Single axle chassis
- Kubota diesel engine, 19 hp, Tier 4
- Length of cable – 3,150 feet
- Type of cable – 3/8" diameter braided steel, "anti-twist"
- Electronic measuring system (TM 3000 – US version)
- Fully enclosed compartment
- Radio remote control
- Deflection boom

Standard features:

- Double capstan system (both capstan heads are driven)
- Large drum capacity for long rope lengths
- Hydrostatic drive for capstan system and rope drum
- This is not a chain-driven system



KE-SP 3050

General specifications:

- Pulling force – 11,000 lbs.
- Single axle chassis
- Yanmar diesel engine, 36 hp, Tier 4 Final
- Length of cable – 3,150 feet
- Type of cable – 1/2" diameter braided steel, "anti-twist"
- Electronic measuring system (TM 3000 – US version)
- Fully enclosed compartment
- Radio remote control
- Deflection boom

Standard features:

- Double capstan system (both capstan heads are driven)
- Large drum capacity for long rope lengths
- Hydrostatic drive for capstan system and rope drum
- This is not a chain-driven system

Underground puller



KE-SP 60100

General specifications:

- Pulling force – 22,000 lbs.
- Tandem axle chassis
- Kohler diesel engine, 56 hp, Tier 4 Final
- Length of cable – 3,150 feet
- Type of cable – 5/8" diameter braided steel, "anti-twist"
- Electronic measuring system (TM 3000 – US version)
- Fully enclosed compartment
- Deflection boom

Standard features:

- Double capstan system (both capstan heads are driven)
- Large drum capacity for long rope lengths
- Hydrostatic drive for capstan system and rope drum
- This is not a chain-driven system



FEATURES

SYSTEM TM 3000® electronic measuring system with USB port and printer

Wireless remote control



Technical data	KE-SP 2030	KE-SP 3050	KE-SP 60100
Drive	Hydraulic	Hydraulic	Hydraulic
Engine	3 cylinder, 19 hp diesel with electric start, Tier 4	3 cylinder, 36 hp diesel with electric start, Tier 4 Final	3 cylinder, 56 hp diesel with electric start, Tier 4 Final
Pulling force	6,700 lbs	11,000 lbs	22,000 lbs
Pulling speed	0-165 ft/min. (pulling-in) 0-200 ft/min. (paying-out)	0-165 ft/min. (pulling-in) 0-200 ft/min. (paying-out)	0-80 ft/min.
Usable cable length	3,150 ft	3,150 ft	3,150 ft
Cable diameter	3/8"	1/2"	5/8"
Overall length	133"	166"	182"
Width	73"	70"	72"
Overall Height	64"	65"	71"
Overall Weight	3,836 lbs	4,520 lbs	7,750 lbs.

Rocky Mountain Region (800) 430-7130
705 West 62nd Avenue – Denver, Colorado 80216

West Coast Region (877) 541-6702
3321 Airport Road – Sacramento, California 95834
www.GlobalMachinery.com

US Dealer



**GLOBAL
MACHINERY**

SPECIALIZED UTILITY EQUIPMENT